

AVAIL™

AVAIL & Azure Active Directory Integration

Reference &
Instruction Guide



AVAIL™ & Azure Active Directory Integration

Reference & Instruction Guide

Version: 20221017

Table of Contents

Overview	3
Your Azure Active Directory & AVAIL	4
Configuring AVAIL in Azure	5
Registering the AVAIL Application	5
Granting Permissions	8
Configuring the Manifest	10
Creating the Publisher Role Group	14
Overview	14
Creating the AVAIL Publishers Group	15
Submit Information to AVAIL	19
Tenant ID	20
Application ID	21
Object ID	22
SAML-P Sign-On Endpoint	23
Publisher Group Object ID	25
Installing AVAIL	27
Overview	27
EXE Installation	28
MSI Installation	29
The ADFS.config file	31
Support	32

Overview

This document will guide you through the necessary steps for configuring AVAIL with Azure Active Directory for your organization.


Generally, the document guides through the following tasks:

- How to configure AVAIL as a custom application within your Azure AD.
 - You can assign all users, a subset of users, or an existing group in your company Azure AD to this application.
- How to configure a dedicated Publishers group within your Azure AD.
 - You will be assigning users and/or existing groups (e.g. a BIM Managers group) in your Azure AD to this new Publisher group.
 - All users that are assigned to the AVAIL application within your Azure AD are able to sign in to AVAIL. The Publisher group that is defined in your Azure AD will be translated such that any member of that group will have Publisher privileges within the AVAIL application, such as creating channels, indexing content into channels, and managing and curating tags on content.
 - Any user that is not a member of that Publisher group, but is assigned to the AVAIL application, defaults to a Consumer role.
- How to deploy the AVAIL Desktop software.
 - During the deployment process, you include installer switches that are associated with your Azure AD. When the software is deployed with these switches, it places a special config file on each user's machine that contains info about the AVAIL application that you set up in Azure.
 - When the user launches the AVAIL software, the user is presented with your company's Azure login dialog.

Your Azure Active Directory & AVAIL

Your Azure Active Directory (AD) will establish a trust relationship with AVAIL. Because of this trust relationship, AVAIL is able to accept this token and authenticate the user. Your Azure AD will use a token-signing certificate to digitally sign all security tokens that it produces. Because each security token is digitally signed by your Azure AD federated services, AVAIL can verify that the security token was in fact issued by you and that it was not modified. This helps prevent attackers from forging or modifying security tokens to gain unauthorized access to resources.

(1) When a user launches the AVAIL application on their workstation, (2) AVAIL retrieves the necessary authority issuer endpoint for (3) requesting a security token from your Azure AD. (4) AD provides a token that contains information about the user requesting access to AVAIL then (5) sends the token to the AVAIL web service. (6) AVAIL will request a token-signing certificate upon receiving the token from your federation URI, which is then (7) returned to validate the token. (8) Once the token is verified, AVAIL will parse the claims extracted from the token and determine what actions the user is authorized to perform, and then (9) return those as claims back down to the AVAIL application.




Configuring AVAIL in Azure

In this section, you will be registering the AVAIL Application, configuring the application with certain permissions, and defining an AVAIL Publishers group all within your Azure Active Directory Portal.

Registering the AVAIL Application

1. From the main navigation bar, select Azure Active Directory, then **App registrations**.



2. Click + New application registration.

The screenshot shows the Microsoft Azure portal interface for 'AVAIL Solutions, Inc.' under the 'App registrations' section. The left-hand navigation pane includes options like 'Create a resource', 'Home', 'Dashboard', and various service categories. The main content area features a search bar, a '+ New registration' button (highlighted with a red box), and tabs for 'Endpoints', 'Troubleshooting', and 'Got feedback?'. Below these, there is a welcome message and a warning about legacy app registrations. A table header is visible with columns for 'DISPLAY NAME', 'APPLICATION (CLIENT) ID', 'CREATED ON', and 'CERTIFICATES & SECRETS'. The table is currently empty, with a message stating 'There are no applications here.' and a 'Register an application' button.

3. In the registration form located in the right-hand region, enter in the values shown in the table below. Click **Create** to complete the registration.

Key	Value
Name	AVAIL
Application Type	Public client (mobile & desktop)
Sign-on URL	https://getavail.com

Microsoft Azure

Dashboard > AVAIL Solutions, Inc. > App registrations > Register an application

Register an application

*** Name**
The user-facing display name for this application (this can be changed later).

AVAIL

Supported account types
Who can use this application or access this API?

Accounts in this organizational directory only (AVAIL Solutions, Inc.)
 Accounts in any organizational directory
 Accounts in any organizational directory and personal Microsoft accounts (e.g. Skype, Xbox, Outlook.com)

[Help me choose...](#)

Redirect URI (optional)
We'll return the authentication response to this URI after successfully authenticating the user. Providing this now is optional and it can be changed later, but a value is required for most authentication scenarios.

Public client (mobile & desktop) | https://getavail.com


By proceeding, you agree to the [Microsoft Platform Policies](#)

Register

Granting Permissions

Now that the AVAIL Application has been created in Azure, you will next need to grant permission to sign in and read the user's profile.


1. In the **AVAIL** application menu, select the **API permissions** option.



- In the **API permissions** page, enable the following API Permissions by click the **+Add a permission** button, under the **Microsoft Graph API**:

API / Permission name	Type
email	Delegated
offline_access	Delegated
openid	Delegated
profile	Delegated
User.Read	Delegated
Groups.Read.All	Delegated

- In the **API permissions** page, click **Grant admin consent for AVAIL Solutions, Inc.**
 - If you are prompted “Do you want to grant consent for the requested permissions below for all accounts?”, select **Yes**.




Configuring the Manifest

1. Navigate back to the **App Registrations** section and click on the **AVAIL** application.


The screenshot shows the Microsoft Azure portal interface for 'AVAIL Solutions, Inc. - App registrations'. The left-hand navigation pane includes sections for 'Create a resource', 'Home', 'Dashboard', 'All services', 'FAVORITES', 'All resources', 'Resource groups', 'App Services', 'Function App', 'SQL databases', 'Azure Cosmos DB', 'Virtual machines', 'Load balancers', 'Storage accounts', 'Virtual networks', 'Azure Active Directory', 'Monitor', 'Advisor', 'Security Center', 'Cost Management + Billing', and 'Help + support'. The 'App registrations' section is selected in the left pane. The main content area displays a table of applications. A notification banner at the top reads: 'Welcome to the new and improved App registrations (now Generally Available). See what's new →'. Below this, a warning message states: 'Looking to learn how it's changed from App registrations (Legacy)? Learn more. Still want to use App registrations (Legacy)? Go back and tell us why.' The table below has columns for 'DISPLAY NAME', 'APPLICATION (CLIENT) ID', 'CREATED ON', and 'CERTIFICATES & SECRETS'. One application is listed: 'AVAIL' with application ID '00aa65a9-5fb5-4f72-937c-9a844cdee05' and creation date '5/29/2019'.

DISPLAY NAME	APPLICATION (CLIENT) ID	CREATED ON	CERTIFICATES & SECRETS
AVAIL	00aa65a9-5fb5-4f72-937c-9a844cdee05	5/29/2019	-


2. In the AVAIL Application area, click **Manifest**.



3. In the **Edit manifest** area in the JSON listed, you should see an item called **“groupMembershipClaims”**. Change the value from **null** to **“SecurityGroup”**.



4. Click **Save** at the top of the **Edit manifest** section.



The screenshot shows the Microsoft Azure portal interface for editing an application manifest. The page title is "AVAIL - Manifest". At the top, there are buttons for "Save", "Discard", "Upload", and "Download". The "Save" button is highlighted with a red box. Below the buttons, there is a text box containing the following JSON manifest:

```
1 {
2   "id": "3e0491f4-91e1-40bb-8d1c-18eb4123e983",
3   "acceptMappedClaims": null,
4   "accessTokenAcceptedVersion": null,
5   "addIns": [],
6   "allowPublicClient": null,
7   "appId": "08aa65a9-5fb5-4f72-937c-9a844cdeeaa05",
8   "appRoles": [],
9   "oauth2AllowUrlPathMatching": false,
10  "createdAt": "2019-05-29T13:16:39Z",
11  "groupMembershipClaims": "SecurityGroup",
12  "identifierUris": [],
13  "informationalUris": {
14    "termsOfService": null,
15    "support": null,
16    "privacy": null,
17    "marketing": null
18  },
19  "keyCredentials": [],
20  "knownClientApplications": [],
21  "logoutUrl": null,
22  "name": "AVAIL",
23  "oauth2AllowIdTokenImplicitFlow": false,
24  "oauth2AllowImplicitFlow": false,
25  "oauth2Permissions": [],
26  "oauth2RequirePostResponse": false,
27  "optionalClaims": null,
28  "orgRestrictions": [],
29  "parentalControlSettings": {
30    "countriesBlockedForMinors": [],
31    "legalAgeGroupRule": "Allow"
32  },
33  "passwordCredentials": [],
34  "preAuthorizedApplications": [],
35  "publisherDomain": "getavall.com",
36  "replyUrl": {
37    "url": "http://getavall.com",
38  }
39 }
```

Creating the Publisher Role Group

Overview

AVAIL supports two primary application roles: Publisher and Consumer. Publishers are generally those who manage content on your network, such as your BIM Managers. Publishers have the ability to create channels, index content into those channels, and share the channels with others within their plan. Consumers on the other hand can only consume the channels that have been shared with them.

In the [Configuring the Manifest](#) section, you configured the AVAIL Application to be able to read a user's Active Directory group memberships. When AVAIL receives, verifies, and parses the group memberships from the token, it will check to see if that user is a member of a group that you will specify as representing the AVAIL Publisher Role. Upon detecting the user is a member of that group, AVAIL will determine if that user is a Publisher in your plan and provide specific claims back to the AVAIL desktop application. If the user is not a member of this AVAIL Publisher AD group, they will default to the Consumer role in AVAIL.


Note, being an Owner of the group does not convey Publisher permissions, the user must be added as a Member.

We recommend creating a dedicated "AVAIL Publishers" group, but it is absolutely acceptable if you already have an existing AD group in mind (such as a "BIM Managers" group). Every organization is just a little bit different, and we're happy to talk through an appropriate configuration for your company.

Creating the AVAIL Publishers Group

To view or add the groups within your Azure Active Directory Portal:

1. Select the **Azure Active Directory** menu option in the left navigation menu, then select the **Groups** option in the second column.



2. Click the + New group option.


The screenshot shows the Microsoft Azure portal interface. The main content area is titled "Groups - All groups" and displays a table with columns: NAME, OBJECT ID, GROUP TYPE, MEMBERSHIP TYPE, EMAIL, and SOURCE. The table is currently empty, showing "No groups found". A red box highlights the "+ New group" button in the top left corner of the main content area. The left sidebar contains navigation options such as "Home", "Dashboard", "All services", and "FAVORITES". The top navigation bar includes the Microsoft Azure logo and a search bar.

NAME	OBJECT ID	GROUP TYPE	MEMBERSHIP TYPE	EMAIL	SOURCE
No groups found					

3. In the **New Group** form, enter the following values:

Group type	Security
Group name	AVAIL Publishers
Group description	“Publishers of the AVAIL Application”
Membership type	Assigned

To add existing users and/or groups to the AVAIL Publishers group, select the **Members** option in the form. Once added, click the **Select** button.



4. Click the blue **Create** button to finish creating the group.

The screenshot shows the Microsoft Azure portal interface for creating a new group. The main area is titled "New Group" and contains the following fields:

- Group type:** Security
- Group name:** AVAIL Publishers
- Group description:** Publishers of the AVAIL Application
- Membership type:** Assigned
- Owners:** 1 members selected
- Members:** (empty list)

A red box highlights the **Create** button at the bottom left of the main form.

On the right side, the **Add members** panel is open, showing a search bar and a list of services to add to the group:

- AAD Request Verification Service - PROD
- AIGraphClient
- AVAIL
- Azure AD Application Proxy
- Azure Cost Management XCloud
- Azure DevOps

The **Selected members** section shows:

- BIM Managers (with a Remove button)

A **Select** button is located at the bottom right of the "Add members" panel.

Submit Information to AVAIL

You have completed all the necessary steps for the registration of the AVAIL application in your Azure Active Directory Portal. In this section, you will need to share some information with AVAIL regarding the application registration that you have just completed.

There are five values associated with your Azure Active Directory and the AVAIL registered application that you will need to submit: [Tenant ID](#), [Application ID](#), [Object ID](#), [SAML-P Sign-On Endpoint](#), and [Publisher Group Object ID](#). If you need assistance in locating these values, the sections in this chapter will guide you.

Please fill in the information located in the form linked below. Once you have submitted the form, await confirmation from a member of the AVAIL Support team before continuing to the [Installing AVAIL](#) chapter of this instruction document.


[Azure Active Directory Information Form](#)

Tenant ID

To locate the **Tenant ID** of your Active Directory:

1. Select **Azure Active Directory** from the main navigation menu
2. Select the **Properties** option from the menu in the second column.
3. In the Properties area, copy the **Tenant ID** that is listed by clicking the blue copy button and paste it into the [form](#).

Note: Directory ID (pictured below) is now called Tenant ID



Application ID

To locate the **Application ID** of the AVAIL application:

1. Select **App Registrations** in the left navigation menu
2. Select the **AVAIL** application row to display the properties slideout region on the right.
3. In the application slide-out region, copy the value of the Application ID listed and paste it into the [form](#).
 - Note: Remain in this view for the [Object ID](#).


The screenshot shows the Microsoft Azure portal interface. The left navigation pane is open, and 'App registrations' is selected. The main content area shows the 'AVAIL Solutions, Inc. - App registrations' page. A table lists the registered applications:

DISPLAY NAME	APPLICATION (CLIENT) ID	CREATED ON	CERTIFICATES & SECRETS
AVAIL	00aa65a9-5fb5-4f72-937c-9a844cdea05	5/29/2019	-

Object ID

To locate the **Object ID** of the AVAIL application:


1. Select **App Registrations** in the left navigation menu.
2. Select the **AVAIL** application row to display the properties slideout region on the right.
3. In the application slide-out region, copy the value of the Application ID listed and paste it into the [form](#).



SAML-P Sign-On Endpoint

To locate the **SAML-P Sign-On Endpoint**:

1. Select **App Registrations** in the left navigation menu.
2. Select the **Endpoints** button located at the top of the application list. A slide-out region will display on the right listing available endpoints.



(continued on next page)

3. Click the blue copy button to copy the **SAML-P SIGN-ON ENDPOINT** value and paste it into the [form](#).


The screenshot shows the Microsoft Azure portal interface. The main content area displays the 'Endpoints' page for an application registration. The application name is 'AVAIL' with ID '00aa65a9'. The 'Endpoints' section lists several endpoints, including 'SAML-P sign-on endpoint' and 'SAML-P sign-out endpoint'. The 'SAML-P sign-on endpoint' is highlighted, and a 'Copy to clipboard' button is visible next to it. The URL for this endpoint is <https://login.microsoftonline.com/464c943-0539-4723-91e9-7c094a06a83/saml2>.

Publisher Group Object ID

The **Publisher Group Object ID** is the identifier of the Active Directory group that will be used by AVAIL's web services to determine if a user within your plan has publishing privileges. If you have not created or determined what group will be the AVAIL Publisher group, please read the [AD Group Memberships & the AVAIL Publisher Role](#) section in this document.


To access the **Object ID** of the Publisher Group:

1. Click the **Azure Active Directory** menu option in the left navigation menu
2. Select the **Groups** option in the second column. A list of groups will be listed in the main region of the portal.
3. Select the **AVAIL Publishers** group in the list to view the group's properties.



(continued on next page)

4. Highlight the **Object ID** of this group, then copy and paste it into the [form](#).



Installing AVAIL

NOTE: Before continuing this section, you must provide AVAIL with the necessary values prior to deploying the AVAIL application across your organization. Please fill in the values in the form located in the [Submit Information to AVAIL](#) section.

Once you have completed the form, please wait for confirmation from the AVAIL Support team before continuing this instruction document.

Overview

Once you have supplied the necessary values to AVAIL and have received confirmation, you will need to inform your assigned AVAIL Support team member of your preferred method of installation: .msi ([MSI Installation](#)) or .exe ([EXE Installation](#)). Prior to installing AVAIL on your user's workstations, you will need to configure your software deployment process to include specific installer switches.

During installation, the switches defined in the sections of this chapter will create a special configuration file titled **ADFS.config** on each workstation. This file is critical for providing the AVAIL desktop application with special values for authenticating users through your Active Directory. You will need the values for the **Application ID** and the **SAML-P Sign-On Endpoint** that you found earlier in the [Submit Information to AVAIL](#) chapter.

It is highly recommended that you first perform a test installation with the defined installer switches prior to deploying AVAIL. In the sections below, there are examples provided which will show you how to install via command line.

EXE Installation

AVAILInstaller.exe

This file packages the AVAIL Desktop application and the Microsoft Visual C++ 2015 Redistributable (x64) into a single installer. The switches below are the values written in the [ADFS.config file](#) upon installing AVAIL.

Switches

- DisableUpdates=1
- ActiveDirectory=1
- ActiveDirectoryVersion="ADFS3"
- ActiveDirectoryAuthority="[Your SAML-P Sign-On Endpoint]"
- ActiveDirectoryRealm="[Application ID]"
- ActiveDirectoryClientId="[Application ID]"
- ActiveDirectoryRedirectUri="https://getavail.com"

Example

```
C:\>"C:\AvailInstaller.exe" /i /quiet /norestart DisableUpdates=1 ActiveDirectory=1
ActiveDirectoryVersion="ADFS3"
ActiveDirectoryAuthority="https://login.microsoftonline.com/4c5bf2ea-7b9d-4fff-ab3a-5182900cab07/saml2" ActiveDirectoryRealm="42fc3910-509f-4b8f-b023-b417a855c526"
ActiveDirectoryClientId="42fc3910-509f-4b8f-b023-b417a855c526"
ActiveDirectoryRedirectUri="https://getavail.com"
```

MSI Installation

In order to properly install the AVAIL application via MSI installation, you will need to deploy one .exe installer and one .msi installer in the following order:

1. *vc_redist.x64.exe* (optional, see below)
2. *Avail.msi*

1. vc_redist.x64.exe

The *vc_redist.x64.exe* file is the Microsoft Visual C++ 2015 Redistributable (x64) and installs run-time components of Visual C++ libraries. These components are required to run C++ applications that are developed using Visual Studio 2015 Update 3 RC and link dynamically to Visual C++ libraries.

Note that many modern applications, such as Autodesk Revit® 2018 (or greater), also require the Microsoft Visual C++ Redistributable package and a supported newer version **may already be installed**.

Switches

- /i /quiet /norestart

Example

```
C:\>"C:\vc_redist.x64.exe" /i /quiet /norestart
```

2. AVAIL.msi

The *Avail.msi* is the installer for the AVAIL Desktop application. The switches below are the values written in the [ADFS.config file](#) upon installing AVAIL.

Switches

- DISABLEUPDATES=1
- ACTIVEDIRECTORY=1
- AD_VERSION="ADFS3"
- AD_AUTHORITY="[Your SAML-P Sign-On Endpoint]"
- AD_REALM="[Your Application ID]"
- AD_CLIENT_ID="[Your Application ID]"
- AD_REDIRECT_URI="https://getavail.com"

Example

```
C:\>msiexec.exe /i "C:\Avail.msi" /quiet /norestart DISABLEUPDATES=1
ACTIVEDIRECTORY=1 AD_VERSION="ADFS3"
AD_AUTHORITY="https://login.microsoftonline.com/4c5bf2ea-7b9d-4fff-ab3a-5182900cab07/saml2" AD_REALM="42fc3910-509f-4b8f-b023-b417a855c526"
AD_CLIENT_ID="42fc3910-509f-4b8f-b023-b417a855c526"
AD_REDIRECT_URI="https://getavail.com"
```

The ADFS.config file

After installing with the switches defined (either msi or exe), a special configuration file titled **ADFS.config** will be created on each workstation. This file is located in the same install location as the AVAIL.exe application (C:\Program Files\AVAIL). This file is a crucial component for providing the AVAIL desktop application with special values for authenticating users via your Active Directory.

Example

A proper, Azure-based ADFS.config file should look something like this:

```
<adfsSettings>
  <add key="ActiveDirectoryVersion" value="ADFS3"/>
  <add key="ActiveDirectoryAuthority" value="[Your SAML-P Sign-on Endpoint]"/>
  <add key="ActiveDirectoryRealm" value="[Your Application ID]"/>
  <add key="ActiveDirectoryClientId" value="[Your Application ID]"/>
  <add key="ActiveDirectoryRedirectUri" value="https://getavail.com"/>
</adfsSettings>
```

Support

Have a question?

Email us at support@getavail.com

or call us at +1 859-963-1616

AVAIL Solutions, Inc.

163 East Main Street

3rd Floor

Lexington, KY 40507

USA

Website: www.getavail.com

Phone: +1 859-963-1616

Email: support@getavail.com